



TRIDENT MIRROR

1495

PARTS INCLUDED

- 1 Trident Mirror Assembly
- 1 Hardware Kit, Including:
 - 1 5/16"-18 X 1-1/2" Button Socket Cap Screw
 - 2 5/16" Split Lock Washers
 - 2 5/16" Flat Washers
 - 1 Double End Threaded Stud
 - 1 1/2" Chrome Spacer
 - 1 1/4" Chrome Spacer
 - 1 5/16" Acorn Nut
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND NOTICES REGARDING THE USE AND CARE OF THIS PRODUCT.

NOTICE

This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

NOTICE

IF INSTALLING THIS PRODUCT FOR ANOTHER PARTY, PLEASE MAKE SURE THEY RECEIVE THIS COPY OF THE INSTALLATION INSTRUCTIONS SO THEY ARE AWARE OF THE IMPORTANT INFORMATION CONTAINED IN THEM.

TOOLS SUGGESTED

Set of Hex Wrenches, Set of Combination Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1

Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

NOTE: Mirror adapters (sold separately) are required for installation on metric cruisers.

NOTICE

Avoid damage to the motorcycle. Protect painted surfaces with a soft cloth or blanket.

STEP 2

Remove the stock mirror from the hand controls; set it aside, it will not be re-used.

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Küryakyn warrants that any Küryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Küryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
 - The product must be properly installed, maintained and operated under normal conditions.
 - Küryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
 - Küryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Küryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Küryakyn and a customer.
- Küryakyn products are often intended for use in specific applications. Küryakyn makes no warranty if a Küryakyn product is used in applications other than intended.
- Küryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Küryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.

• Küryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Küryakyn. Küryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

For purchasing Küryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Küryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Küryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Küryakyn USA® All Rights reserved.





MOUNTING STUD INSTALLATION

- STEP 2** Mount the mirror assembly to the short threaded end of the mounting stud and tighten.
- STEP 3** Install one split lock washer and one flat washer over the long end of the mounting stud. PIC 1
- STEP 4** Insert the mounting stud through the mirror mounting hole, if the mounting stud is too long, use the included spacers to shorten the length of the exposed threads.
- STEP 5** Secure the stud from the bottom side using the spacer(s) if needed, then the flat washer, split lock washer and the acorn nut. Finger tighten for now.
- STEP 6** Adjust the mirror as desired. The mounting arm is adjustable by loosening the fastener (PIC 2) on the front side and rotating the arm higher or lower.
- STEP 7** Once the mirror is positioned as desired, tighten all fasteners.
- STEP 8** Adjust the mirrors for proper view before riding the motorcycle.

NOTICE Ensure that the position of the mirror and stem **DO NOT** interfere with the operation of the motorcycle hand controls.

NOTICE It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not provide warranty coverage on products or components lost due to improper installation or lack of maintenance. Periodic inspection and maintenance are required on all fasteners.



H-D MOUNTING SINGLE SCREW

- STEP 2** From the bottom side, insert the button socket cap screw with a split lock washer and flat washer through the mirror mounting hole, if the cap screw is too long and bottoms out in the mirror before it gets tight, use the included spacers to shorten the length of the exposed threads.
- STEP 3** Place a flat washer then the split lock washer over the spacer(s), if used, on the protruding end of the cap screw.
- STEP 4** Thread the cap screw in to the mirror mount, leave finger tight for now.
- STEP 5** Adjust the mirror as desired. The mounting arm is adjustable by loosening the screw (PIC2) on the front side and rotating the arm higher or lower.
- STEP 6** Once the mirror is positioned as desired, tighten all fasteners.
- STEP 7** Adjust the mirrors for proper view before riding the motorcycle.

NOTICE Ensure that the position of the mirror and stem **DO NOT** interfere with the operation of the motorcycle hand controls.

NOTICE It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not provide warranty coverage on products or components lost due to improper installation or lack of maintenance. Periodic inspection and maintenance are required on all fasteners.