



# INSTALLATION

## PRE-FILTER/RAIN SOCK

## 9335

### PARTS INCLUDED

- 1 Pre-Filter/Rain Sock for Pro-R Hypercharger
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

### THANK YOU FOR CHOOSING KÜRYAKYN!

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND NOTICES REGARDING THE USE AND CARE OF THIS PRODUCT.**

<b>WARNING</b>	<b>THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.</b>
<b>NOTICE</b>	<b>This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.</b>
<b>CAUTION</b>	<b>This indication alerts you to the fact that ignoring the contents described herein can result in potential injury.</b>

**NOTICE**

**IF INSTALLING THIS PRODUCT FOR ANOTHER PARTY, PLEASE MAKE SURE THEY RECEIVE THIS COPY OF THE INSTALLATION INSTRUCTIONS SO THEY ARE AWARE OF THE IMPORTANT INFORMATION CONTAINED IN THEM.**

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let cool.

**WARNING**

**YOU WILL BE WORKING AROUND THE ENGINE AND EXHAUST SYSTEM DURING INSTALLATION. ENSURE THAT THE ENGINE AND EXHAUST SYSTEM HAVE FULLY COOLED TO PREVENT INJURY.**

**STEP 2** Place the elastic opening of the Pre-Filter/RainSock over the back of the Hypercharger until the end of the Hypercharger fits into the formed end of the Pre-Filter/Rain sock. PIC 1 Stretch the Pre-Filter forward and around the front of the Hypercharger. PIC 2

-cont.-

9335-21MC-0413

### CUSTOMER SERVICE

877.370.3604 (toll free)

### INSTALLATION QUESTIONS

techsupport@kuryakyn.com  
or call 715.247.2983

### LIMITED WARRANTY

Küryakyn warrants that any Küryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Küryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
  - The product must be properly installed, maintained and operated under normal conditions.
  - Küryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
  - Küryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Küryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Küryakyn and a customer.
- Küryakyn products are often intended for use in specific applications. Küryakyn makes no warranty if a Küryakyn product is used in applications other than intended.
- Küryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Küryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.
- Küryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Küryakyn. Küryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

### ABOUT OUR CATALOG

For purchasing Küryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Küryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Küryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Küryakyn USA® All Rights reserved.



kuryakyn.com

**CARE AND USE OF THE PRE-FILTER/RAIN SOCK**

- Küryakyn uses only oiled gauze filters from K&N and AFE. These filters remain fully functional and effective in rain and inclement weather.
- The Pre-Filter/Rain Sock can be used:
- If riding in the rain for extended periods of time
- To help keep insects and other debris from accumulating on the gauze filter
- To reduce exposure of the gauze filter to soapy water or high pressure spray when washing the motorcycle.
- The Pre-Filter/Rain Sock is made from water repellant and UV resistant fabric.
- The Pre-Filter/Rain Sock will filter debris down to .005 size particles.
- The Pre-Filter/Rain Sock should be removed and cleaned with hot soapy water and rinsed with clean water once a month or every 3000 miles if used on a continuous basis.

PIC 1



PIC 2

**CAUTION**

Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

**NOTICE**

Constant contact of the Pre-Filter/Rain Sock and the Hypercharger can cause damage to the finish of the Hypercharger.

**NOTICE**

During extended use of the Pre-Filter/Rain Sock, dirt and grime may collect between it and the hypercharger. This will cause damage to the air cleaner finish. Make sure to remove and clean the Pre-Filter Rain Sock on a regular basis.

**NOTICE**

Use of the Pre-Filter/Rain Sock may slightly reduce air flow and horsepower.

**NOTICE**

Use of this Pre-Filter/Rain Sock may cause scratches or dulling of the finish of the air cleaner cover. Küryakyn WILL NOT be responsible for incidental or consequential damages from the use of this Pre-Filter/Rain sock.

*Ride On!*